

Blokkade

Special fencing system, developed in co-operation with some of the largest insurance companies to help solve the problem of theft and ram-raids.

Provides protection against vehicles being driven off forecourts, through open or closed showroom windows and as terrain protection to storage or open areas.

Height

600mm as standard.

Construction

Two versions are available, heavy or standard duty. Heavy duty has re-inforced posts. Posts are set 900mm deep in the ground and 1.50m apart. Too small for cars to drive through, with a rail at 600mm above ground too high to lift motorcycles with ease.

Can be installed with open entry points at any location or blocked off to form gate using lockable sliding rail insert and removable central post.

Subtle, but effective protection without the uninviting looks of a high fence.

Surface Treatment

- Hot dip galvanised as standard:
- Option; additionally powder coated:
 - (i) Standard RAL colour:
 - (ii) Any RAL colour:



Blokkade

Type	Height	Posts	Insert	Rail	Opening
Standard	600mm	Ø89x2.5mm	n	Ø60.3x1.75mm	Ø51x2.25mm
Heavy	600mm	Ø89x4.00mm	y	Ø60.3x1.75mm	Ø51x5.0mm



Citadel

Unit F1, Halesfield 4,
Telford, Shropshire TF7 4AP, England
Tel: +44 (0) 1952 410 020
Fax: +44 (0) 1952 411 144
E-mail: mail@citadelsecurityuk.com
www.citadelsecurityuk.com