

CODI 3C

The assured system, that can be used where perimeter demarcation and more robust higher levels of security are required than the standard 3D system.

Uses include, Government, Utilities, Industry, School, Sports, Play Grounds and Domestic.

Design

Open mesh panel with pressed beams for additional strength gives a strong aesthetically pleasing finish.

Panels secured to hollow section posts using individual clamps.

Panels

Panels 2000mm & 2400mm with a length of 3.00m long as standard.

2.00m high 3No & 2.40m high 4 No pressed horizontal beams.

Mesh size 200 x 30mm.

Wire size Ø5mm horizontal wires and Ø5mm Vertical wires

Posts

Posts are spaced at 3.02m centres as standard, using 60x60mm RHS. Length 2.70m long or 3.10m long dependant upon panel height.

Post/Panel connection

A mounting block with clamp and M8 anti-tamper screw fixing.

Surface Treatment

- Galvanised and additionally powder coated:
 - (i) Standard RAL colour:
 - (ii) Any RAL colour:



TECHNICAL SPECIFICATION



Citadel

Unit F1, Halesfield 4,
Telford, Shropshire TF7 4AP, England
Tel: +44 (0) 1952 410 020
Fax: +44 (0) 1952 411 144
E-mail: mail@citadelsecurityuk.com
www.citadelsecurityuk.com