

Olympiade

Tennis Court Fencing system—TA.

Construction

Steel posts and rails are used clad with chainlink. * Option Carrade MR weldmesh rolls Available 3.00m & 1.00m high standards. Other heights on application.

Court Sizes

- 18m x 36m
- 34m x 36m
- 50m x 36m

Construction

- Posts $\varnothing 60 \times 1.75$ mm CHS set at 3.00m centres. Corner posts $\varnothing 89 \times 2.5$ mm CHS. Top rail $\varnothing 41.5 \times 2$ mm CHS.
- Cladding Chainlink 40x40mm mesh, $\varnothing 3$ mm wire *Option 3.7mm wire plastic coated.
- Option Raking panel 3.00m to 1.00m when "Bedstead" layout chosen. (3.00m high ends with 1.00m sides)
- Gates: Opening 1.25m single or 2.50m double, height 2.00m. $\varnothing 38 \times 2$ mm CHS frame with 50x50x4mm weldmesh infill, welded to frame. Includes $\varnothing 60.3 \times 2.5$ mm CHS posts, 180° opening hinges, drop bolt on double gate & mortise lock.

Surface Treatment

- Galvanised as standard:
- Option; additionally powder coated: standard RAL colour Green:



TECHNICAL SPECIFICATION



Citadel

Unit F1, Halesfield 4,
Telford, Shropshire TF7 4AP, England
Tel: +44 (0) 1952 410 020
Fax: +44 (0) 1952 411 144
E.mail: mail@citadelsecurityuk.com
www.citadelsecurityuk.com