

Swing Gates

To match railing and weldmesh fence systems

Design

Standard construction frame 60x60mm RHS with infill to match requirements of each B&G fencing system. Mortise lock, 180° opening adjustable hinges and integral drop bolts used as standard.

Sizes

Heights - to match fencing systems
 Width—Single gate from 1.00m to 5.00m opening
 Or 2.00m to 10.00m opening double leaf.

Characteristics

Industrially manufactured, high quality finish, minimum maintenance.

Surface Treatment

- Hot dip galvanised as standard:
- Option; additionally powder coated:
 - (i) standard RAL colour:
 - (ii) Any RAL colour:



Swing gate		Clear opening		Post	Frame	Brace
Single	Double	Single	Double	section		
1000	2000	1010	2060	80x80x3	60x60x2	
1250	2500	1310	2660	"	"	
1500	3000	1610	3260	"	"	
2000	4000	2070	4180	100x100x4	"	
2500	5000	2520	5090	110x110x5	"	
3000	6000	2970	5990	"	"	
3500	7000	3570	7190	"	"	x
4000	8000	4020	8080	140x140x5	"	x
5000	10000	5070	10180	"	"	x
mm	mm	mm	mm	mm	mm	



Citadel

Unit F1, Halesfield 4,
 Telford, Shropshire TF7 4AP, England
 Tel: +44 (0) 1952 410 020
 Fax: +44 (0) 1952 411 144
 E-mail: mail@citadelsecurityuk.com
 www.citadelsecurityuk.com