

ALL-Liner – “Plug n Play”

Characteristics.

A new concept providing a rapid and easy to install gate solution for anyone requiring a cantilever gate. A gate opening can be made secure in minutes.

Gate wing is factory assembled with the running wheels mounted on a simple frame that is fixed using bolts to any suitable surface or foundation.

The drive unit requires connection to a 230V power supply.

Safety features: Comply with CE regulations, safety contact strips and warning light. *Option Photocell.

Controls: Wireless remote with 2 No transmitters and a key switch on guide post.

Designed and constructed to give extremely long lifetime through above average reliability of the gate assembly and its individual components. Gate leaf 100% Aluminium, supports and posts made in steel.

Available - Manual or Automated.

Sizes (Single leaf)

Standard openings:- 3.00m to 10.00m

Standard Heights:- 1.00 to 2.50m.

Infill

Barricade - Ø30mm @ 150mm c/c

*option dragon tail anti-climb edge.

Rondissade - Ø30mm @ 150mm c/c

Stockade - 25mmx25mm @ 150mm c/c

Construction

Bottom beam 300mm x 200mm.

Frame 115mm x 80mm.

Posts 120x120x3mm RHS.

Surface Treatment

Natural Aluminium and galvanised steel powder coated:

(i) From standard RAL colours:

(ii) Any RAL colour.



Gate is easily craned into position and bolted to finished surface

Ground frame & Power Operation
24Volt Motor, rack & pinion drive with control board mounted in a weather proof housing.



Citadel

Unit F1, Halesfield 4,
Telford, Shropshire TF7 4AP, England
Tel: +44 (0) 1952 410 020
Fax: +44 (0) 1952 411 144
E.mail: mail@citadelsecurityuk.com
www.citadelsecurityuk.com