

Telescopic - Sliding gates for restricted spaces.

Characteristics.

A reliable robust gate range that offers flexibility of design for applications with restricted areas to operate. Gates can be in filled using tubular steel bars, weldmesh or made solid.

Available - Manual or Automated.

Infill

Barricade - Ø26 or 30mm @ 150mm c/c
*option dragon tail anti-climb edge.

Rondissade - Ø26mm @ 150mm c/c

Stockade - 25mmx25mm @ 150mm c/c

Carrade - Ø8/6/8mm, 200x50mm mesh

Atlas - 358

Other infill on request.

Construction

Rectangular and square hollow section steel, sizes to suit application

Opening

Widths (single):- 3.00 - 4.00 - 5.00 - 6.00 - 7.00 - 8.00 - 9.00 - 10.00 - 11.00 - 12.00m.

Widths (double):- 6.00 - 8.00 - 10.00 - 12.00 - 14.00 - 16.00 - 18.00 - 20.00 - 22.00 - 24.00m.

Other openings on request

Height

1.00 to 3.00m.

Other heights on request

Foundation

Base plates at finished ground level and running track to cast into foundation.

Or

Cantilevered.

Surface Treatment

(i) Hot dip galvanised.

(i) Additional powder coating in standard RAL colour:

(ii) Any RAL colour

(iii) Cold zinc spray to steel powder



Above 15.00m opening gate opens into 8.50m space

Below 5.00m opening gate opens into 2.75m space



Citadel

Unit F1, Halesfield 4,
Telford, Shropshire TF7 4AP, England
Tel: +44 (0) 1952 410 020
Fax: +44 (0) 1952 411 144
E-mail: mail@citadelsecurityuk.com
www.citadelsecurityuk.com